



## TECHNICAL DATA DELAIR<sup>®</sup> ETSILINE

### Introduction Pressurizers Etsiline 32, 52 and 102

Each delair<sup>®</sup> Etsiline pressurizer is equipped with two heat-regenerated adsorbers, an air compressor, a pressure relief valve and a microprocessor controlled printed circuit board. The combination results in an attractive pressurizer which is suitable for fully continuous and automatic operation

### Etsiline 32, 52 and 102

### Model A

Microprocessor controlled printed circuit board	•
Digital display:	
- Digital pressure indication	•
- Analogue pressure indication	•
- Operating time indication	•
- Process read out	•
Programmable pressure level	
- standard pressure ranges (factory set)	20 - 30 mbar
Other pressure ranges on request	40 - 80 mbar
Outlets, each equipped with shut-off valve Tubing 6 mm OD, other connections on request	6
Remote pressure sense input	•
Optical dew point indication	•
Safety relief valve	•
Electrical fuse	•
Humidity alarm	optional
Low pressure alarm	•
Mounting:	
- ETSI-rack	•
- 19" rack	•
- Wall mounting	•
- Floor/table mounting	•

**NEW**



Digital display



6 Outlets

## Standard specifications

Medium	Ambient air
Operation	Fully automatic and continuous
Location	Indoors
Enclosure	IP 40
Ambient temperature	-10°C - +45°C
Relative humidity	Max. 95%
Outlet dew point Full load, 23°C inlet, 83% R.H.	< -40°C
Power supply	110V, 230V, 50/60 Hz 24V, 48V, 60V DC
Drying time	6 hours
Regeneration time	3 hours
Stand-by time	depending on requirements

## Technical data

Model	Configuration	Outlet capacity l/h	Power consumption			Sound level db(A)	Dimensions			Weight kg
			Drying	Regeneration	Stand-by		Width	Depth	Height	
			W	W	W		mm	mm	mm	
delair® Etsiline 32	ETSI-rack 19" rack Wall mounting Floor/table mounting	30	9	53	5	< 43	535	200	221,5	10
							482.6	200	221.5	
							420	234	221.5	
							420	200	243.5	
delair® Etsiline 52	ETSI-rack 19" rack Wall mounting Floor/table mounting	50	9	53	5	< 43	535	200	221.5	10
							482.6	200	221.5	
							420	234	221.5	
							420	200	243.5	
delair® Etsiline 102	ETSI-rack 19" rack Wall mounting Floor/table mounting	100	13	59	5	< 43	535	200	221.5	12
							482.6	200	221.5	
							420	234	221.5	
							420	200	243.5	

**NEW**



ETSI-rack



19" rack



Wall mounting



Floor/table mounting

